VALRIYA

SPEC GRADE COMMERCIAL LED LIGHTING

CLIENT
PROJECT
NOTES

ASP1 SERIES

SQUARE STRAIGHT STEEL POLE

The ASP1 Series features a weldable grade hot rolled commercial quality carbon steel tubing with a minimum yield strength of 42,000 PSI. Consisting of a thermoset polyester powder coat that is applied to a minimum of 3-5 mils.

- Shaft meeting minimum yield strength of 42,000 PSI
- Base plate meeting minimum yield strength of 36,000 PSI
- 2-Piece ABS base cover L11.42″ × W11.42″ × H5″
- Removable die-cast aluminum pole cap



TECHNICAL DETAILS

POLE	Commercial Welded Steel Pipe
BASE PLATE COVER	ABS Plastic
FINISH	View Ordering Guide
EPA RATINGS	View Pg.3
CERTIFICATIONS	TAA

BASE PLATE

4″ ANCHOR BASE



BOLT CIRCLE RANGE 8 - 11
BOLT PROJECTION 3.75″

5″ ANCHOR BASE



BOLT CIRCLE RANGE 10.6 - 12
BOLT PROJECTION 4.875″

ASP1 SERIES
SQUARE STRAIGHT STEEL POLE

VALRIYA
SPEC GRADE COMMERCIAL LED LIGHTING

ORDERING GUIDE

Example: VA-ASP1-411-25-10-343-BZ

VA-ASP1 — [ ] — [ ] — [ ] — [ ] — [ ] — [ ]

SHAFT
[4] 4″
[5] 5″

GAUGE
[11] 11g - 1/8″
[7] 7g - 3/16″

HEIGHT
[15] 15ft [1]
[20] 20ft [1]
[25] 25ft
[30] 30ft [2]
[XX] Custom Height

BASE [3]
[10] 10.5″
[11] 11″

ANCHOR
[341] 3/4″ x 17″ (up to 20ft poles)
[343] 3/4″ x 30″ (21ft - 25ft poles)
[136] 1″ x 36″ (26ft - 30ft poles)

FINISH
[BZ] Bronze
[BK] Black
[WH] White
[GN] Green
[GY] Gray
[SM] Silver
[C] Custom

POLE CAP
[4SPC] 4″ Square Pole Cap
[5SPC] 5″ Square Pole Cap

BASE COVER
[4SBC] 4″ Square Base Cover
[5SBC] 5″ Square Base Cover

OPTIONS
[HC] Handhole Cover

[1] Poles up to 20ft use only [11] 0.180″ Gauge [2] Poles over 25ft use only [7] 0.120″ Gauge [3] Poles up to 25ft use [10] 10″ Base, Poles over 25ft use [11] 11″ Base

ANCHOR BOLTS



ASP1 SERIES
SQUARE STRAIGHT STEEL POLE

VALRIYA
SPEC GRADE COMMERCIAL LED LIGHTING

EPA RATINGS

POLE HEIGHT	EPA FT² W/ 1.3 GUST FACTOR																SHAFT SIZE	WALL THICK	GAUGE	WEIGHT
	80 MPH	MAX LBS	90 MPH	MAX LBS	100 MPH	MAX LBS	110 MPH	MAX LBS	120 MPH	MAX LBS	130 MPH	MAX LBS	140 MPH	MAX LBS	150 MPH	MAX LBS				
10'	30.6	765	23.8	595	18.9	470	14	325	10.5	263	8.5	213	7	175	6	150	4"	0.120	11	76lbs
15'	17.9	450	13.5	335	10.3	250	7.2	185	6	145	4.4	112	3.3	85	2.4	60	4"	0.120	11	113lbs
20'	9.6	240	6.7	165	4.5	150	2.5	100	2.5	62	1.5	38	-	-	-	-	4"	0.120	11	138lbs
25'	4.8	150	2.6	100	1	50	-	-	-	-	-	-	-	-	-	-	4"	0.120	11	170lbs
30'	10.7	267	6.7	167	3.9	100	1	25	-	-	-	-	-	-	-	-	5"	0.179	7	380lbs

SCREW POSITIONING PLATE

4" PLATE



5" PLATE



DRILL DETAILS



INTERNAL DIAGRAM