

CLIENT

PROJECT

NOTES



SFL SERIES

SPORT FLOOD LIGHT

The SFL Series is a high-performance flood light with a heavy duty IP65 housing designed to withstand harsh and extreme outdoor conditions. Ideal for Stadiums, Arenas, Baseball Fields, Tennis Courts, Driving Ranges, and Parks.

- Available in NEMA 3Hx3V, 4Hx4V, and 5Hx5V distributions
- Versatile mounting bracket for hassle free installation
- Available in 3 different color temperatures
- UL, IP65



TECHNICAL DETAILS

POWER SMALL	505W, 600W
POWER LARGE	600W, 650W, 850W
COLOR TEMPERATURE	4000K, 5000K, 5700K
CRI	70+ CRI
VOLTAGE	120-277VAC, 347-480VAC
EFFICIENCY	Up to 146lm/w
DIMMING	1-10V
LUMENS	Up to 118,000lm
HOUSING	Aluminum
MOUNTING	Trunnion
OPERATING TEMPERATURE	-40°F to 131°F
WARRANTY	10 Years
FINISH	Black
LOCATION	Wet
CERTIFICATIONS	UL, IP65



LUMENS 5700K

SMALL	505W	600W	
	70,000lm	82,000lm	
LARGE	600W	650W	850W
	84,000lm	91,000lm	118,000lm



L70: 100,000+ HOURS

DIMENSIONS

SMALL



LARGE



WEIGHT:

505W: 39.3lbs
 S 600W: 40.9lbs
 L 600W: 56.3lbs
 650W: 63.5lbs
 850W: 63.5lbs

SFL SERIES

SPORT FLOOD LIGHT

ORDERING GUIDE

Example: VA-SFL-LV600-SB50-N44-TR

VA-SFL						TR
	VOLTAGE	SIZE / POWER	FINISH	CCT	DISTRIBUTION	MOUNT
	[LV] 120-277VAC [HV] 347-480VAC	[505S] Small / 505W [600S] Small / 600W [600L] Large / 600W [650L] Large / 650W ¹ [850L] Large / 850W	[B] Black [C] Custom	[40] 4000K [50] 5000K [57] 5700K	[N33] 3Hx3V [N44] 4Hx4V [N55] 5Hx5V ²	[TR] Trunnion
¹ Only available in [HV] 347-480VAC ² Only available in [850L] Large / 850W						

ACCESSORIES*

SKU	DESCRIPTION
VA-SFL-LS	Laser Sight ²
VA-SFL-BV	Black Visor ²
VA-SFL-WV	White Visor
VA-SFL-GS	Glare Shield
VA-SFL-TA	Tenon Adapter

ACCESSORIES




VA-SFL-LS

VA-SFL-TA








VA-SFL-BV

VA-SFL-WV

VA-SFL-GS

*Items must be ordered separately ² Included as standard option

DISTRIBUTION TYPES

3HX3V

4HX4V

5HX5V

SFL SERIES

SPORT FLOOD LIGHT

VALRIYA
SPEC GRADE COMMERCIAL LED LIGHTING

SKU	DESCRIPTION	WATTAGE	CCT	LUMENS	VOLTAGE ¹	EPA	DLC	QUICK SHIP
VA-SFL-X505-SB40-N44-TR	Small, 4Hx4V	505W	4000K	70,000	120-277VAC or 347-480VAC	0.8218	Pending	No
VA-SFL-X505-SB50-N44-TR	Small, 4Hx4V	505W	5000K	70,000	120-277VAC or 347-480VAC	0.8218	Pending	No
VA-SFL-X505-SB57-N44-TR	Small, 4Hx4V	505W	5700K	68,000	120-277VAC or 347-480VAC	0.8218	Pending	No
VA-SFL-X600-SB40-N44-TR	Small, 4Hx4V	600W	4000K	82,000	120-277VAC or 347-480VAC	0.8218	Pending	No
VA-SFL-X600-SB50-N44-TR	Small, 4Hx4V	600W	5000K	82,000	120-277VAC or 347-480VAC	0.8218	Pending	No
VA-SFL-X600-SB57-N44-TR	Small, 4Hx4V	600W	5700K	80,000	120-277VAC or 347-480VAC	0.8218	Pending	No
VA-SFL-X600-LB40-N33-TR	Large, 3Hx3V	600W	4000K	80,640	120-277VAC or 347-480VAC	1.2413	Pending	No
VA-SFL-X600-LB40-N44-TR	Large, 4Hx4V	600W	4000K	84,000	120-277VAC or 347-480VAC	1.2413	Pending	No
VA-SFL-X600-LB50-N33-TR	Large, 3Hx3V	600W	5000K	80,640	120-277VAC or 347-480VAC	1.2413	Pending	No
VA-SFL-X600-LB50-N44-TR	Large, 4Hx4V	600W	5000K	84,000	120-277VAC or 347-480VAC	1.2413	Pending	No
VA-SFL-X600-LB57-N33-TR	Large, 3Hx3V	600W	5700K	78,720	120-277VAC or 347-480VAC	1.2413	Pending	No
VA-SFL-X600-LB57-N44-TR	Large, 4Hx4V	600W	5700K	82,000	120-277VAC or 347-480VAC	1.2413	Pending	No
VA-SFL-X650-LB40-N33-TR	Large, 3Hx3V	650W	4000K	87,360	347-480VAC	1.2413	Pending	No
VA-SFL-X650-LB40-N44-TR	Large, 4Hx4V	650W	4000K	91,000	347-480VAC	1.2413	Pending	No
VA-SFL-X650-LB50-N33-TR	Large, 3Hx3V	650W	5000K	87,360	347-480VAC	1.2413	Pending	No
VA-SFL-X650-LB50-N44-TR	Large, 4Hx4V	650W	5000K	91,000	347-480VAC	1.2413	Pending	No
VA-SFL-X650-LB57-N33-TR	Large, 3Hx3V	650W	5700K	84,480	347-480VAC	1.2413	Pending	No
VA-SFL-X650-LB57-N44-TR	Large, 4Hx4V	650W	5700K	88,000	347-480VAC	1.2413	Pending	No
VA-SFL-X850-LB40-N33-TR	Large, 3Hx3V	850W	4000K	113,280	347-480VAC	1.2413	Pending	No
VA-SFL-X850-LB40-N44-TR	Large, 4Hx4V	850W	4000K	118,000	347-480VAC	1.2413	Pending	No
VA-SFL-X850-LB50-N33-TR	Large, 3Hx3V	850W	5000K	113,280	347-480VAC	1.2413	Pending	No
VA-SFL-X850-LB50-N44-TR	Large, 4Hx4V	850W	5000K	118,000	347-480VAC	1.2413	Pending	No
VA-SFL-X850-LB57-N33-TR	Large, 3Hx3V	850W	5700K	107,520	347-480VAC	1.2413	Pending	No
VA-SFL-X850-LB57-N44-TR	Large, 4Hx4V	850W	5700K	112,000	347-480VAC	1.2413	Pending	No